

Comfortable and ergonomic opening of safety doors

Door handle actuator for SAFEMASTER STS

Machines and plants which are safeguarded by protective fences must be entered at regular intervals for maintenance work or for troubleshooting. With the door handle actuator, convenient and ergonomic opening of doors and safety guards is possible on these machines and plants without compromising safety. The movable, self-adjusting actuator allows the closing elements to be offset by up to 20 mm. This ensures full functionality, even with doors that have been set down or are bent. At the same time, up to three padlocks can be hung in the open position to ensure protection against accidental locking. The stable door handle can be used for left and right hinged doors and can be rotated in 90° steps if a horizontal handle position is not possible due to the system. Optionally, the door handle actuator can also be equipped with a door handle on the inside.

- Self-adjusting up to 20 mm for large tolerances
- Optionally with coded actuator against manipulation
- Optionally with handle on the inside
- Escape release with safety switch (SX module) possible



1.151 characters (incl. spaces)

We would be very pleased about a free publication of the text and the pictures.

Kontaktadresse zur Veröffentlichung
Contact address for publication
Nous contacter avant publication, s.v.p.

E.DOLD & Söhne KG
Postfach 1251
78114 Furtwangen

Tel.+49 (0)7723/654-0, Fax –356
E-mail: dold-relays@dold.com
Website: www.dold.com
Ansprechpartner: Bastian Beha